

MERIROAD
RC90-221 DTG

For road and construction
- all year-round



MERIROAD

MERIROAD

RC90-221 DTG

For road and construction
- all year-round

MERIROAD WORKING ENVIRONMENTS

- Crushing the ground before stabilizing,
- Preparing the subsoil for laying sett (car parks, roads, residential areas)
- Recycling of old asphalt and gravel roads.
- Stabilization of grounds down to a depth of 50 cm on all types of roads, with easily accessible materials like cement, polimers, ash, dolomite, lime,
- Construction and redoing of forest roads, communal roads,

FEATURES

- Bolt mounted hydraulically adjustable counter blades
- Hardox liner (frame) bolt mounted
- UNTH Rotor with cost effective carbide cutters and bolt on wear protection for the holders
- POC - Pressure operated safety clutch (SUOKONE patented)
- Hydraulically adjusted side plates for working depth control
- Hydraulic screen for sieving and sizing the material
- Hydraulic front & rear door for material control

OPTIONS

- Hydraulic Top Link
- Multiple cutter options available
- Water spraying system

Tractor demand

Mounting	CAT 3
Auxiliary hydraulic	4pcs. 2-acting
Auxiliary hydraulic	12v euro soccet for additional outputs
PTO	1000 rpm
Working speed	Creeper gear recommended

Technical data:

Power range	280 - 550 hp
Transmission	Mechanical PTO
Final transmission	Gear (G-serie)
Clutch	POC-3 XL
Rotor diameter / width	850 / 2230 mm
Cutter qty.	106 + 32 pc
Working depth	0-45cm
Free cutting depth adjustable	6 - 25cm

Main dimensions:

Length	2365 mm
Width	2820 mm
Height	1770 mm
Weight	5900 kg



SUOKONE OY
Lastaajantie 1
88610 Vuokatti

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com