

MERICRUSHER

MJ-1.8 ST / DT

For versatile crushing



MERICRUSHER

MERICRUSHER

MJ-1.8 ST / DT

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting
- Clearing of power lines
- Clearing of firebreaks

AGRICULTURE

- Clearing of farm land
- Reclaiming soil for farming
- Farm road maintenance
- Orchard clearing

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame)
- STD, STE or UNV4 Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor

OPTIONS

- Push bar (hydraulic)
- Rear roller (hydraulic)
- Guide plate (front fixed)
- Hydraulic Top Link
- Multiple cutter options available

Base machine demand

Tractor	
Mounting	CAT-2
Auxiliary hydraulic	2 pcs. double acting
PTO	(540) / 1000 rpm
Working speed	Creep gear recommended

Technical data:

Power range ST /DT	70-90 hp	90-180 hp
Transmission	Mechanical PTO	
Final transmission	Chain 2-row	
Clutch	POC-2	
Rotor diameter / width	400 / 1750mm	16 / 69 inch
Cutter qty.	76 (T25 Rotor)	
Working depth	200 mm / 8 inch	

Main dimensions:

Length	1550 mm	61 inch
Width	2200 mm	87 inch
Height	1220 mm	48 inch
Weight ST / DT	970 / 1060 kg	2140 / 2340 lbs
Weight, with options ST / DT	1390 / 1480 kg	3070 / 3260 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com