

MERICRUSHER

MJ-2.3 ST / DT

For versatile crushing



MERICRUSHER

MERICRUSHER

MJ-2.3 ST / DT

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of farm land
- Reclaiming soil for farming
- Farm road maintenance
- Orchard clearing

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame)
- STD, STE or UNV4 Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting
- Clearing of power lines
- Clearing of firebreaks

OPTIONS

- Push bar (hydraulic)
- Rear roller (hydraulic)
- Guide plate (front fixed)
- Hydraulic Top Link
- Multiple cutter options available

Base machine demand

Tractor	
Mounting	CAT-2
Auxiliary hydraulic	3 pcs. double acting
PTO	(540) / 1000 rpm
Working speed	Creep gear recommended

Technical data:

Power range ST /DT	70-90 hp	90-150 hp
Transmission	Mechanical PTO	
Final transmission	Chain 2-row	
Clutch	POC-2	
Rotor diameter / width	400 / 2250mm	16 / 89 inch
Cutter qty.	96 (T25 Rotor)	
Working depth	200 mm / 8 inch	

Main dimensions:

Length	1550 mm	61 inch
Width	2700 mm	106 inch
Height	1220 mm	48 inch
Weight ST / DT	1080 / 1230 kg	2380 / 2710 lbs
Weight, with options ST / DT	1580 / 1730 kg	3480 / 3810 lbs

