

MERICRUSHER

MJFS-241 STX / DTX

For versatile crushing



MERICRUSHER

MERICRUSHER

MJFS-241 STX / DTX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTH Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Bolt mounted lift arm brackets

OPTIONS

- Slip alarm (12V)
- Rotating sizing screen (hydraulic front / rear)
- Rear roller (hydraulic)
- Guide plate (fixed front / hydraulic rear)
- Hydraulic Top Link
- Multiple cutter options available

Base machine demand

Tractor	
Mounting	CAT-3
Auxiliary hydraulic	4 pcs. double acting
PTO	1000 rpm
Working speed	Creeper gear recommended

Technical data:

Power range STX / DTX	280 - 400 hp	280 - 700 hp
Transmission	Mechanical PTO	
Final transmission	Gear (X-serie)	
Clutch	POC-3 XL	
Rotor diameter / width	800 / 2440mm	32 / 96 inch
Cutter qty. base + side	100 + 24 (UNTH Rotor)	
Working depth	400 mm / 16 inch	

Main dimensions:

Length	3090 mm	122 inch
Width STX / DTX	2860 / 3010 mm	113 / 119 inch
Height	1750 mm	69 inch
Weight STX / DTX	3740 / 4360 kg	8245 / 9610 lbs
Weight, with options STX / DTX	5150 / 5860 kg	11350 / 12920 lbs

