

MERICRUSHER

MJHS-241 DTX

For versatile crushing



MERICRUSHER

MERICRUSHER

MJHS-241 DTX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT, UNTH or STB Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Slip alarm (12V)
- Rotating sizing screen (hydraulic front/rear)
- Door type sizing screen (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link

Base machine demand

Tractor	
Mounting	CAT-3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creep gear recommended

Technical data:

Power range	400 - 700 hp	
Transmission	Mechanical PTO	
Final transmission	Gear (X-serie)	
Clutch	POC-3 XL	
Rotor diameter / width	600 / 2410mm	24 / 95 inch
Cutter qty.	110 (T25 STB Rotor)	
Working depth	300 mm / 12 inch	

Main dimensions:

Length	2540 mm	100 inch
Width	2990 mm	117 inch
Height	1430 mm	57 inch
Weight	2950 kg	6500 lbs
Weight, with options	4000 kg	8820 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com