MERICRUSHER

MJHS-311 STX

For versatile crushing







MERICRUSHER

MERICRUSHER

MJHS-311 STX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- -Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt monted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTH Rotor with cost effective carbide cutters
- POC Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Bolt mounted lift arm brackets

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Slip alarm (12V)
- Sizing screen rotating (hydraulic front/rear)
- Sizing screen door type (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- -Hydraulic Top Link
- Multiple cutter options available

Base machine demand		
Tractor		
Mounting	CAT-3	
Auxiliary hydraulic	3 pcs. double acting	
PTO	1000 rpm	
Working speed	Creeper gear recommended	
Technical data:		
Power range	200 - 400 hp	
Transmission	Mechanical PTO	
Final transmission	Gear (X-serie)	
Clutch		POC-3 XL
Rotor diameter / width	600 / 3110mm	24 / 122 inch
Cutter qty. base + side	130 + 12 (UNTH Rotor)	
Working depth	300 mm / 12 inch	
Main dimensions:		
Length	2540 mm	100 inch
Width	3610 mm	142 inch
Height	1430 mm	57 inch
Weight	2850 kg	6280 lbs
Weight, with options	4300 kg	9500 lbs



