

MERICRUSHER

MJHS-311 DTX

For versatile crushing



MERICRUSHER

MERICRUSHER

MJHS-311 DTX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTH Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Slip alarm (12V)
- Rotating sizing screen (hydraulic front/rear)
- Door type sizing screen (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link

Base machine demand

Tractor	
Mounting	CAT 3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creeper gear recommended

Technical data:

Power range	400 - 700 hv
Transmission	Mechanical PTO
Final transmission	Gear (X-serie)
Clutch	POC-3 XL
Rotor diameter / width	600 / 3110mm 24 / 122 inch
Cutter qty.	134 (T25 UNTH Rotor)
Working depth	300 mm / 12 inch

Main dimensions:

Length	2540 mm	100 inch
Width	3610 mm	142 inch
Height	1430 mm	57 inch
Weight	3250 kg	7200 lbs
Weight, with options	4630 kg	10200 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com