

MERIROAD
RC65-241 DTG

For versatile crushing



MERIROAD

MERIROAD

RC65-241 DTG

For versatile crushing

MERIROAD WORKING ENVIRONMENTS

- Crushing the ground before stabilizing,
- Preparing the subsoil for laying sett (car parks, roads, residential areas)
- Recycling of old asphalt and gravel roads.
- Stabilization of grounds down to a depth of 35 cm on all types of roads, with easily accessible materials like cement, polimers, ash, dolomite, lime,
- Construction and redoing of forest roads, communal roads, drives to agricultural areas.
- Building outdoor feed pads
- Stump removal

FEATURES

- Bolt mounted adjustable counter blades
- Hardox liner (frame) bolt mounted
- UNTH Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Hydraulic front & rear door for material control

OPTIONS

- Hydraulic Top Link
- Slip Alarm 12V
- Rear roller (hydraulic)

Base machine demand

Tractor	
Mounting	CAT 3
Auxiliary hydraulic	2-3 pcs. Double acting
PTO	1000 rpm
Working speed	Creeper gear recommended

Technical data:

Power range	160 - 400 hp
Transmission	Mechanical PTO
Final transmission	Gear (G-serie)
Clutch	POC-3
Rotor diameter / width	600 or 650 / 2410mm 24 or 26 / 95 inch
Cutter qty. base + sides	98+12 (UNTH Rotor)
Working depth	350 mm / 14 inch

Main dimensions:

Length	1570 / 2580 mm	67 / 101 inch
Width	2860 mm	112 inch
Height	1450 mm	58 inch
Weight	3250 kg	7150 lbs
Weight, with rear roller	3750 kg	8250 lbs

