Meri RT-600 TT

Professional land levelling and profiling





MERI RT-600 TT

Professional land levelling and profiling

Meri Screw levellers are designed for efficient land profiling and clearing. In the handling of large earth masses, screw levellers have a class of their own in terms of capacity. Screw levellers can be used on both mineral and peat-based soild.

The RT-600 TT is a towable screw leveller that is pulled behind the tractor. Designed for large scale earth mass handling. Typical applications are: clearing of new farm land, rehabilitation and profiling of existing farm land, leveling of excavated earth piles from the ditches. The machine is equipped with a Utility Model Rights protected auger with shape locked bolt on wear liners, where extreme wear is taken into account.

EQUIPMENT

FEATURES

- Double boggie
- Auger bolt mouted shape locked wear liners
- POC Pressure operated safety clutch (SUOKONE patented)

OPTIONS

Road transportation kit

Base machine demand	
Powerful four wheel tractor	
Mounting	Towable draw bar
Auxiliary hydraulic	3 pcs. 2-way
РТО	1000 rpm
Working speed	Creeper gear recommended
	0,5-7km/h
Technical data:	
Power range	150 - 250 hp
Transmission	Mechanical PTO
Final transmission	Gear
Clutch	POC-3
Auger diameter	950mm / 37 inch
Auger width (working)	6000mm / 236 inch
Boggie diameter / width	750 / 1500mm 30 / 59 inch
Main dimensions:	
Working L / W / H	5890x7000x1750mm / 232x276x69inch
Transport L / W / H	8815x3375x2650mm / 347x133x104inch
Weight (work)	5820kg / 11650lbs
Weight (transport)	6000kg/ 13250lbs



